

PCT Appl. No: PCT/SE2005/000123

Due date: 2006-03-12

To
Patent- och registreringsverket
STOCKHOLM

INTERNATIONAL SECTION

International Patent Application No: PCT/SE2005/000123

Applicant: MIRCONA AB

Svar på föreläggande den 8 september 2004 i svensk patentansökan nr. 0400211-9

We hereby file a new set of claims, a new description and abstract substituting which are meant to form the basis of the continuing prosecution.

Claim 1 has been redrafted so that the new claim now comprises features from old claim 2 and 7.

Claims 2, 7, 9 and 10 have been deleted and the description and abstract have been adapted to the reworked claims.

By letting the viscoelastic material attach to a bearer material and thus having a sandwich-composite-like composition, one gets a construction that discloses a much drastically improved damping effect. This is particularly obvious when combining the viscoelastic material with a relatively soft bearer material such as a soft metal, e.g. aluminum. The multi-layer construction greatly improves the damping effect. Every contact surface contributes to the energy loss and hence the damping of the vibrations.

Handläggs av: Johan Löfstedt, MDG
Aktnummer: 110101801
Tel.nr: 08 729 95 00
Fax nr: 08-31 83 15

D1 discloses a tool holder with a vibration damping adhesive between its tool holding outer part and the shaft. There is however no vibration damping material on its envelope surface which surface is adapted to be arranged in a machine tool.

D2 discloses a vibration damping material with a base stock layer. There is nowhere mentioned, however, that this layer is adapted to attach to a surface of any apparatus. Instead is the opposed layer, the release layer, adapted to be removed from an adhesive layer which is meant to be attached to the construction to be vibration damped. Thus, there is no mention or implication that this material is adapted to be applied between two constructions to impede vibrations to transfer from one construction to another.

To combine the tool holder of D1 with the material of D2 is thus not possible. Even if the material would be suitable to insert between the two parts of the tool holder in D1 it would still not result in a construction according the present claim 1.

Thus, the invention according to the new claim 1 is new and does involve an inventive step and is therefore patentable.

The claims 2-8 are dependent on claim 1 and thus also patentable.

Stockholm 23 February 2006

MIRCONA AB

gm

Zacco Sweden AB



Johan Löfstedt

Vibration-damped Tool Holder

TECHNICAL AREA

The present invention relates to a vibration-damped tool holder.

BACKGROUND TO THE INVENTION

5 Tool holders in manufacturing machines have a tendency to vibrate and give rise to noise when in use. Such vibration disturbs the work process by having a negative effect on the accuracy of the result. The vibrations also give rise to a troublesome disturbing noise that worsens the environment around the manufacturing machine.

A perfect manufacturing machine does not give rise to any vibrations, and all energy
10 is passed to the process that is to be carried out. In practice, vibrations always arise when the various parts of the machine work against each other. As the machine becomes more and more worn, changes in its dynamic properties take place. This means that new types of vibration can arise during different periods of the lifetime of the machine. The vibrations can lead to poor surface finish of the work piece, further wear on the machine and on tools, with,
15 in the worst case, irreparable damage as a consequence.

During the processing of metal materials, problems also arise that are caused by the high level of noise caused by vibrations from the processing and the noise of the machine. Tools that have been used up until the present have not had built-in or subsequently added damping arrangements of such a type that sufficient damping of sound and vibration has
20 been possible. It is important to be able to remove major parts of the vibration noise within the frequency interval that is uncomfortable for the human ear. It is desirable that the level is reduced to a level under 80 dB.

The arrangement of a vibration-damping material in a longitudinal track on a tool holder is previously known through US 2426359. The aim is to completely damp the
25 vibrations, or at least to reduce them significantly.

A tool holder is previously known through WO 02/45892 A1 (Figure 14) with a damping element. The distance between the damping element and the tool body is such that a relative motion between the tool body and the damping element is permitted during processing.

30 A tool holder for several tools is previously known through US 5033340 A. An aperture is present in the connecting surface between each tool and the tool holder, and a "damping sandwich" construction is arranged in this aperture. This design consists of alternating layers of steel and viscoelastic material. It is considered that this design reduces noise.

35 Previous attempts to solve the problem of vibrations have thus contained complicated solutions with weights and fluids in cavities in the tool holder intended to oscillate with inverted phase relative to the undesired vibrations and in this way to cancel

them out. Other solutions demonstrate material arranged on the surface of the tool holder intended in the same manner to oscillate with inverted phase for cancellation of the vibrations. These solutions in general involve troublesome dimensioning procedures and testing procedures before the correct material and properties are found, even if this is possible at all.

One aspect of the present invention is thus to achieve a tool holder with the conditions required to damp vibrations in a simpler manner.

BRIEF DESCRIPTION OF THE INVENTION

The present invention, therefore, demonstrates a shaft intended to be arranged in a tool holder in a manufacturing machine, a head on which a cutter is intended to be arranged and a viscoelastic material arranged such that the cutter is in contact with the manufacturing machine solely via the viscoelastic material. At least those parts on the surface of the shaft that are intended to be in contact with the manufacturing machine are provided with the viscoelastic material, and the viscoelastic material is attached on a bearer material that is attached to the envelope surface of the shaft.

In one embodiment of the tool holder according to the present invention the viscoelastic material surrounds the surface of the shaft.

In a further embodiment of the tool holder according to the present invention, the viscoelastic material is divided into a number of plates threaded onto the shaft and arranged next to each other.

In a further embodiment of the tool holder according to the present invention a metal tube is arranged externally coaxial with the viscoelastic material intended to absorb and even out the pressure during attachment.

In a further embodiment of the tool holder according to the present invention the viscoelastic material has ridges arranged in tracks in the surface of the shaft running along the longitudinal axis of the shaft.

In a further embodiment of the tool holder according to the present invention the plates are punched out.

In a further embodiment the shaft is provided with a cavity.

In a further embodiment the cavity has been drilled out in the form of a cylinder.

It has become apparent that reductions of 500 to 600% can be obtained with a tool holder according to the present invention, compared to a conventional tool holder.

DESCRIPTION OF DRAWINGS

Figure 1 shows a tool holder according to a first embodiment of the present invention.

Figure 2 shows a tool holder according to a second embodiment of the present invention.

Figure 3 shows a cross-section through a shaft of a modification of the tool holder according to Figures 1 and 2 according to the present invention.

Figure 4 shows a tool holder according to a third embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

With reference to Figure 1, a first embodiment of the invention is constituted by a tool holder 1, consisting of a shaft 2 and a head 3. A cutter is intended to be arranged on the head 3. The shaft 2 of the tool holder 1 is provided with a viscoelastic material 4 around its surface 5. The viscoelastic material 4 in this embodiment is in the form of a sheet or tape, with a thickness of a few tenths of a millimetre, wound around a bearer material, such as an aluminium plate, wound around the surface 5 and attached to this surface with the aid of glue or similar. A non-compulsory iron tube 6 is arranged around the viscoelastic material 4 intended to distribute more evenly the mounting forces when the tool holder 1 is attached to a manufacturing machine. The radius of the shaft 2 can be less than that of the head 3, and the bearer material and the sheet together with the thickness of the steel tube 6 may be equivalent to this difference, which thus ensures that the outer surface of the steel tube is in contact with the surface of the head 3. It is also possible to attach these onto the shaft of a tool holder of conventional design. Furthermore, the viscoelastic material may surround as large a part as possible of the tool holder, something that has proven to give further advantageous damping effects.

With reference now to Figure 2, a second embodiment of the invention is constituted by a tool holder 1. The shaft 2 of the tool holder 1 is provided with a viscoelastic material 4 on its surface 5. The viscoelastic material 4 in this embodiment is designed as a number of plates 7 threaded onto the shaft 2 and arranged next to each other. The plates 7 are attached onto a bearer material, such as an aluminium plate, wound around the surface 5 and attached to this surface with the aid of a glue or similar. A steel tube 6 may or may not be arranged around the plates 7, intended to distribute more evenly the mounting forces when the tool holder 1 is mounted in a manufacturing machine. The radius of the shaft 2 is, in the same way as in the embodiment according to Figure 1, less than the radius of the head 3, such that the outer surface of the steel tube 6 makes contact with the surface of the head 3.

With reference to Figure 3, a modification is displayed that is suitable for both the embodiments according to Figure 1 and Figure 2. The viscoelastic material 4 is in this case provided with longitudinal spline-formed ridges 8 that have equivalent longitudinal tracks 9 in the surface 5 of the shaft. The ridges 8 are glued into the tracks 9. There may be one or several ridges. The modification in Figure 3 shows 3 ridges, which can be regarded as a

suitable number. The ridges 8 are intended to prevent the viscoelastic material/the plates 4/7 rotating around the shaft 2 during operation.

With reference now to Figure 4, a third embodiment of the invention is constituted by a tool holder 1. The tool holder is physically divided into two parts, a forward head 3 intended to accommodate a cutter, and a rear shaft 2 intended to be mounted into a manufacturing machine. The shaft 2 and the head 3 are separated from each other by a viscoelastic material 4. The viscoelastic material 4 is attached to each of the two parts 2, 3 by gluing. The viscoelastic material 4 may be arranged at any location on the tool holder between the attachment of the cutter into the front end of the tool holder and the region intended for mounting into the manufacturing machine. It is preferable that the viscoelastic material 4 is arranged at the front end in the manner that is shown in Figure 4. In this embodiment, the viscoelastic material 4 may be in the form of a sheet or tape, with a thickness of a few tenths of a millimetre, and it may also be attached onto a bearer material, such as an aluminium plate, that is attached to one of the parts 2, 3 with the aid of glue or similar. The viscoelastic material is then attached to the other part 2, 3.

It has proven to be the case that the damping properties can be further improved if the shaft of the tool holder is provided with a cavity; preferably in the form of a drilled cylinder.

The vibrations can be cancelled by designing the viscoelastic material in a suitable manner.

Claims

1. A tool holder (1) comprising:

a shaft (2) intended to be arranged in a tool holder in a manufacturing machine;

a head (3) on which a cutter is intended to be arranged; and

5 a viscoelastic material (4) arranged such that the cutter is in contact with the manufacturing machine solely via the viscoelastic material (4), in which at least those parts on the surface (5) of the shaft (2) that are intended to be in contact with the manufacturing machine are provided with the viscoelastic material, characterised in that the viscoelastic material (4) is attached on a bearer material that is attached to the envelope surface (5) of
10 the shaft (5).

2. The tool holder according to claim 1, characterised in that the viscoelastic material (4) surrounds the surface (5) of the shaft (2).

3. The tool holder according to any one of the preceding claims, characterised in that the viscoelastic material (4) is divided into a number of plates (7) threaded onto the shaft
15 (2) and arranged next to each other.

4. The tool holder according to any one of claims 2-3, characterised in that a metal tube (6) is arranged coaxially external to the viscoelastic material (4) intended to absorb and even out the pressure during mounting.

5. The tool holder according to any one of claims 1-4, characterised in that the
20 viscoelastic material (4) has ridges (8) arranged in tracks (9) in the surface (5) of the shaft (2) running along its longitudinal axis.

6. The tool holder according to any one of claims 3-5, characterised in that the plates (7) are punched out.

7. The tool holder according to any one of the preceding claims, characterised in
25 that the shaft (2) is provided with a cavity.

8. The tool holder according to claim 7, characterised in that the cavity is a drilled cylinder.

Abstract

A tool holder 1 comprising a shaft 2 intended to be arranged in a tool holder in a manufacturing machine, a head 3 on which a cutter is intended to be arranged and a viscoelastic material 4 arranged so that the cutter is in contact with the manufacturing machine solely via the viscoelastic material 4, in which at least those parts on the surface (5) of the shaft (2) that are intended to be in contact with the manufacturing machine are provided with the viscoelastic material 4. The viscoelastic material (4) is attached on a bearer material that is attached to the envelope surface (5) of the shaft (5).

10

(Figure 1)